

# C900 Series



## Multimedia Production Platform Devices

- 5+ Color Capability:  
CMYK plus White or Clear<sup>1</sup>
- Handles stock up to 360 gsm,  
3"x5" cards to 13"x52" banners
- Print speeds up to 50 ppm<sup>2</sup>

**NEW** C941dn  
**NEW** C931dn  
**NEW** C911dn



# C900 Series



## Specifications

Model		C941dn	C931dn	C911dn
<b>Performance</b>		5-Color Digital LED		4-Color Digital LED
Print Speed <sup>2</sup>	CMYK/Mono	Up to 50ppm Letter, 27ppm Tabloid		
	CMYK + White	Up to 45 ppm Letter, 24 ppm Tabloid	N/A	
	CMYK + Clear	Up to 18 ppm Letter	N/A	
Time to First Page <sup>2</sup>		Approx. 8 seconds		
Duty Cycle		300,000 pages		
RMPV		25,000 pages		
<b>Print Quality</b>	Resolution	Up to 1200 x 1200 dpi; ProQ 1200 x 600 x 16 levels		
<b>Memory</b>	RAM (Standard/Max)	2 GB		
	Processor	1.2 GHz ARM CPU		1 GHz ARM CPU
<b>Compatibility</b>	Printer Languages	Adobe® PostScript® 3™, PCL® 6, PCL 5c, XPS®		
	Connectivity	High-speed USB 2.0, 10 Base-T/100 Base-TX/1000 Base-T Ethernet		
	Operating Systems	Windows® 8, Windows 7, Windows Vista®, Windows XP, Windows Server 2012, Windows Server 2008, Windows Server 2008 R2, Windows Server 2003; Mac® OS 10.3.9 – 10.9		
	Network Protocols	TCP/IP, EtherTalk		
<b>Color Features/Solutions</b>		EFI® Fiery® XF 5.0 Server (optional external PC-based server)		N/A
		Trapping; Embedded ICC Profile-based workflow; Simulations for SWOP, ISO Coated, Japan Color; PDF Direct Print; PS Gamma Adjust; Color Correct		
<b>Print Management</b>		Print Job Accounting; PrintSuperVision 4.0		
<b>Media Handling</b>	Media Sizes	Tabloid extra (12" x 18"), tabloid (11" x 17"), legal, letter, executive, 3" x 5" index cards, A3, A4, A5, A6, B5, C5, DL, Com 10, Monarch envelopes, and banners (up to 13" by 52")		
	Media Weight	Trays 1/2/3 and High-Capacity Feeder: 52–320gsm; Multi-purpose Tray: 52–360gsm		
Media Capacity	Multi-purpose Tray (MPT)	Up to 310 sheets		
	Trays 1/2/3	Up to 530 sheets		
	High-Capacity Feeder	Up to 1,590 sheets		
Max Capacity		Up to 2,950 sheets (w/ MPT, 2 Trays and High-Capacity Tray)		
Media Output		Face Down: max 610 sheets; Face Up: max 300 sheets		
<b>Environmental</b>	Size (WxDxH)	27.5" x 24.6" x 25.2" (699 mm x 625 mm x 640 mm)		
	Weight	244.4 lbs (110.8 kg) including consumables	215.2 lbs (97.6 kg) including consumables	
	Temperature/Humidity	50°– 90°F (10°– 32°C) / 20% – 80%RH		
	Power Consumption	Active: 1600W max. /1100W avg.; Standby: avg. 40W; PowerSave mode: 30W or less; Sleep mode: 4W or less; Auto Shutoff: 0.4W or less		
	Noise Levels	Active: 57dBA or less; Standby: 34dBA or less; PowerSave mode: Inaudible		
<b>Options</b>	Accessory (Part Number)	530-Sheet 2nd/3rd Tray (45530702); High-Capacity Feeder w/ caster base (45530802); 530-Sheet Tray w/ Caster Base (45530902); White Spot Color Kit (45531302); Clear Spot Color Kit (45531402); EFI® Fiery® XF Server and Software (45592302); 160 GB Hard Disk Drive (44622302)		
<b>Warranty</b>	Limited	C911dn/C931dn: 1-Year On-Site <sup>3</sup> ; C941dn: 90-Day On-Site <sup>3</sup> ; All models: 5-Year Digital LED Printheads		
Product	Description	Part Numbers		
C911dn	4-Station Digital LED Printer	62439901 (120V)		
C931dn	4-Station Digital LED Printer	62440001 (120V)		
C941dn	5-Station Digital LED Printer	62441501 (120V)		
<b>Toner Cartridges</b>	C931dn/C941dn (38,000 pages <sup>4</sup> ) C911dn (24,000 pages <sup>4</sup> ) C941dn (10,000 pages <sup>4</sup> ) C941dn (20,000 pages <sup>4</sup> )	Cyan – 45536515; Magenta – 45536514; Yellow – 45536513; Black – 45536516 Cyan – 45536423; Magenta – 45536422; Yellow – 45536421; Black – 45536424 White – 45536405 Clear – 45536406		
<b>Image Drums</b>	40,000 pages <sup>4</sup> C941dn (20,000 pages <sup>4</sup> ) C941dn (20,000 pages <sup>4</sup> )	Cyan – 45103727; Magenta – 45103726; Yellow – 45103725; Black – 45103728 White – 45103729 Clear – 45103730		
<b>Waste Toner Box</b>	Approx. 40,000 pages <sup>4</sup>	45531502		

<sup>1</sup> C941dn unit only

<sup>2</sup> Published performance results based on laboratory testing of letter-size sheets, simplex. Individual results may vary.

<sup>3</sup> Available in the U.S. and Canada only.

<sup>4</sup> Based on ISO/IEC 19798.

<sup>5</sup> Based on 5% coverage of letter-size sheet, simplex.

<sup>6</sup> Based on 3 pages per job.

Specifications are subject to change without notice.

Featured products may not be available in all countries. Please contact your local office for regional availability.

© 2013 Oki Data Americas, Inc. OKI Reg. T.M., M.D., Oki Electric Industry Co., Ltd. 5+ Color logo T.M., Oki Data Americas, Inc. Single Pass Color and logo Reg. T.M., Oki Data Corp. PANTONE Reg. T.M., PANTONE Certified Printer T.M., Pantone Inc. EFI, Fiery Reg. T.M., EFI Corp. Adobe, PostScript Reg. T.M., PostScript 3 T.M., Adobe Systems, Inc. PCL Reg. T.M., Hewlett-Packard Co. Windows, Windows Vista Reg. T.M., Microsoft Corp. Mac Reg T.M., Apple Inc. ENERGY STAR Reg. T.M., US EPA.

Printed in the USA

MS16094-0913

### OKI DATA AMERICAS, INC.

**USA**  
2000 BISHOPS GATE BLVD.  
MOUNT LAUREL, NJ 08054-4620  
TEL: 800.OKI.DATA (800.654.3282)  
FAX: 856.222.5320

**CANADA**  
4140B SLADEVIEW CRESCENT  
UNITS 7 & 8  
MISSISSAUGA, ONTARIO L5L 6A1  
TEL: 905.608.5000  
FAX: 905.608.5040

[WWW.OKIDATA.COM](http://WWW.OKIDATA.COM)

**OKI**  
Open up your dreams