

PNEUMATIC LAMINATING SYSTEMS

Matrix Pneumatic delivers even faster production times than our standard systems.

KEY FEATURES

- Pneumatic pressure
- Retrofits to existing models
- Easy-to-use control panel
- Anti-curl technology
- Semi-automatic feed
- Automatic seperator

GREAT FOR USE IN

- Commercial printers
- Digital printers
- Copy and print shops

IDEALLY SUITED FOR

Business cards

Book covers Brochures Flyers

and many more...

Menus



Design

The Matrix Pneumatic can run up to twice the speed of our standard systems. Printers can laminate work even faster to get the job finished and back to the customer.

Pneumatic pressure rollers allow you to laminate certain substrates up to 50% quicker, saving both time and cost. The Matrix can be purchased as a complete system, or as a modular retrofit for the multilingual MX-370 and MX-530.

The Pneumatic option is produced in Britain which shortens our supply chains and lead times. We've used the highest quality components within the systems, including Omron switches, Schneider electrics and British built Bambi compressors.



Specifications	MX-370P	MX-530P
Max. Laminating Speed (m/ft/min)	10m/33ft	10m/33ft
Max. Lamination Film Width (mm/inches)	340mm/13″	510mm/20″
Minimum Paper Thickness (gsm/lbs)	135gsm/90lbs	135gsm/90lbs
Maximum Sheet Width (mm/inches)	420mm/17″	550mm/22″
Warm-up Time (mins)	10	10
Temperature Range (°C/°F)	0-140°C/32-284°F	0-140°C/32-284°F
Power Supply (V)	220/240	220/240
Power Supply Required (Amps)	13	13
Power Consumption (W)	2200	2400
Overall Dimensions (mm/inches)	800x1800x1400mm/31x71x55"	900x2050x1400mm/35x81x55"
Gross Machine Weight (Kg/lbs)	190Kg/419lbs	220Kg/485lbs
Warranty*	1 year	1 year

*For full terms & conditions on parts and labour warranty, visit vivid-online.com/support/warranty_information

Vivid Laminating Technologies Ltd

St George's House, Whitwick Road, Coalville, Leicestershire LE67 3FA England

Igland Vivid-online.com

/vividlaminating

0845 1 30 40 50 sales@vivid-online.com



You Aritic

Tube