

# PT SCC Automated Modular Finishing Solution



PT Interchangeable Die system

## FEATURES:

- ✓ Large and easy to use colour, touch screen controls
- ✓ No additional modules required for business cards, perforating or rotary scoring
- ✓ Cross perforation capability is standard
- ✓ 26 sheets per minute (2 cuts/1 crease)
- ✓ Image shift compensation on 2 axis

## SPECIFICATIONS:

Electrical:	208-230VAC 1 Ph 60Hz 20A
Speed:	up to 1560 sph*
Max. Stock Size:	14.5" x 25.5" (37 cm x 65 cm)
Min. Stock Size:	8.25" x 8.25" (21 cm x 21 cm)
Side Trim:	.125" -1.5" (3.2 mm – 38.1 mm)
Head Trim:	.125" - .59" (3.2 mm – 15 mm)
Gutter Slit:	.197" - .59" (3.2 mm x 15 mm)**
Min Cut Length:	
Lead Edge:	.125" (3.2 mm)
Gutter:	.157" (4 mm)
Trail Edge:	.197" (5 mm)

Stock Weight:	150-380 gsm
Maximum Slits:	6/page
Maximum Cuts:	32/page
Maximum Creases:	32/page
Input Tray Capacity:	1.57" (4 cm)
Output Tray Capacity:	1.97" (5 cm)
Barcode Recognition:	Optional
Double Feed Detection:	Yes, Ultrasonic
Control System:	9" colour touch screen, standard with job layout

Interchangeable crease/crossperf dies: Optional

\* varies, actual results dependent upon application, multiple variables affect results

\*\* gutter strips wider than .59" (15 mm) are output to the exit tray



Authorized Graphic Whizard dealer:

[www.graphicwhizard.com](http://www.graphicwhizard.com)

Call toll-free 800-265-3376 for further information.