



# Gfp

**Graphic Finishing**  
partners

**Where Finishing Comes First.**

## **Gfp 865DH-4RS**

### **Versatile Dual Heat Laminator**

For finishing professionals who need versatility, quality, and economy in one machine, the Gfp 865DH-4RS delivers. Turn out thermal encapsulation with low melt films (1.5-10mil), PSA lamination, and mounting jobs quickly and easily.

#### **ULTIMATE FLEXIBILITY**

*Dual heat for thermal & cold apps*

#### **MAXIMIZE PRODUCTIVITY**

*Inline Rotary Slitters*

#### **FAST ROLL CHANGES**

*Front/Rear Swing-out shafts* **EASY**

#### **LOADING**

*3" Quick-Grip Swing-out Shafts*

#### **INDUSTRIAL DESIGN**

*Years of maintenance-free service*



***laminating • mounting • encapsulating***

***Our most flexible, cost-effective laminator yet***

Spend less time on set-ups and changeovers with swing-out Quick-Grip supply shafts. Two front rewind shafts allow thermal encapsulation of prints from a roll.



- Labor saving swing-out supply shafts
- Drop-in Quick-Grip rewind shafts
- Photoelectric eye for operator safety
- Independent top and bottom heaters
- Web clutch adjustment for output quality
- Includes rear rewind with rotary slitters
- Swing-up feed table and 38" output height



Includes motorized rear  
rewind with rotary slitters for  
roll-to-roll applications.

Slitters not for use with  
thermal films.



Media Alignment disks keep  
supply rolls from telescoping

Rugged Design  
Professional Quality  
Proven Performance  
Economically Priced

#### APPLICATIONS

*Signs*  
*Posters*  
*POP Displays*  
*Trade show displays*  
*Dry-erase boards*  
*Graphic mounting*  
*Photo mounting*  
*Floor graphics*  
*Window graphics*  
*Vehicle graphics*

cTUVus  
Safety  
Approval



#### Warranty:

1 year parts & labor.  
**Installation is included.**

### 865DH-4RS

<i>Laminating Width</i>	65"
<i>Roller Diameter</i>	5"
<i>Roller Gap</i>	1"
<i>Main rollers</i>	Silicone
<i>Supply roll diameter(max)</i>	16" bottom, 8" top
<i>Film shafts</i>	3" aluminum Quick-Grip
<i>Rear rewind with rotary slitters</i> (Not for use with thermal films.)	Included
<i>Max. temperature</i>	266°F
<i>Heat method</i>	Quartz heater
<i>Film thickness</i>	1.5 - 10mil
<i>Laminating speed</i>	0-13 ft/min
<i>Drive motor</i>	DC geared motor
<i>Pressure Adjustment</i>	Dual hand wheels
<i>Roller heating</i>	Top & Bottom
<i>Power Supply</i>	240v 60HZ Single phase 24A
<i>Power Consumption</i>	Max. 5760W
<i>Dimensions</i>	87" x 34" x 49"
<i>Net Weight w/ stand</i>	846 lbs.
<i>Shipping Dimensions (L x W x H)</i>	90" x 40" x 63" 1129 lbs.

Your local dealer is:



**Graphic Finishing**  
partners

